

General data Combifloats



Payload	0	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75
C-9.5 Quadra	2.39 0.52	2.22 0.69	2.05 0.86	1.92 0.99	1.78 1.13	1.65 1.26	1.51 1.40	1.38 1.53	1.24 1.67	1.11 1.80	0.89 1.93	0.84 2.07	0.71 2.20	0.57 2.34	0.44 2.47	0.30 2.61
Tri	2.39 0.52	2.19 0.72	2.00 0.91	1.82 1.09	1.64 1.27	1.46 1.45	1.28 1.63	1.10 1.81	0.92 1.99	0.74 2.17	0.56 2.35	0.38 2.53	0.20 2.71			
Duo	2.39 0.52	2.08 0.83	1.78 1.13	1.51 1.40	1.24 1.67	0.97 1.94	0.70 2.21	0.43 2.48								

C-7 Quadra	1.66 0.47	1.52 0.61	1.39 0.74	1.26 0.87	1.12 1.01	0.99 1.14	0.85 1.28	0.72 1.41	0.59 1.54	0.45 1.68	0.32 1.81		
Tri	1.66 0.47	1.43 0.70	1.28 0.85	1.12 1.01	0.94 1.19	0.76 1.37	0.59 1.54	0.41 1.72	0.23 1.90				
Duo	1.66 0.47	1.39 0.74	1.12 1.01	0.85 1.28	0.59 1.54	0.32 1.81							

C-5 Quadra	1.16 0.36	1.03 0.49	0.89 0.63	0.76 0.76	0.62 0.90	0.49 1.03	0.35 1.17		
Tri	1.16 0.36	0.99 0.53	0.80 0.72	0.62 0.90	0.44 1.08	0.26 1.26			
Duo	1.16 0.36	0.89 0.63	0.62 0.90	0.35 1.17					



Technical data

UNIT	C-5				C-7				C-9.5			
X = 0.14	L	B	H	W	L	B	H	W	L	B	H	W
	[m]	[m]	[m]	[Ton]	[m]	[m]	[m]	[Ton]	[m]	[m]	[m]	[Ton]
Quadra	12.20	3.05	1.52	13.10	12.20	3.05	2.13	17.10	12.20	3.05	2.91	20.00
Tri	9.15	3.05	1.52	9.70	9.15	3.05	2.13	13.65	9.15	3.05	2.91	15.50
Duo	6.10	3.05	1.52	6.90	6.10	3.05	2.13	9.04	6.10	3.05	2.91	11.10
Allowable	C-5				C-7				C-9.5			
Pull on each coupling	30				45				45 [Tons]			
Deck load	15				15				15 [Tons/m²]			



www.combifloat.com