

General

Type C-7 Modular Holding Spud Barge

Dimensions, hull

Length 24.40 m
 Breadth 15.25 m
 Depth 2.13 m
 Free deck area approx. 350 m²

Loads*

Variable deck load 375 mT, 0.60 meter freeboard
 Suitable for 80 – 90 ton crawler crane
 Deck strength 15 mT/m²

Spud system

No. of spuds Three (3) holding spuds
 Spud handling Electrically lifted, gravity lowered
 Leg length 18.00 m, up to 15.00 m water depth



Scope of Supply

5 pcs. C-7 Quadra float, 12.20 x 3.05 x 2.13m
 2 pcs. C-7 Tri float, 9.15 x 3.05 x 2.13m
 7 pcs. C-7 Duo float, 6.10 x 3.05 x 2.13m
 3 pcs. C-7 30" Holding spud well, incl. winch, wire, socket, controls
 3 pcs. C-7 30" Holding spud leg, 18.00m
 4 pcs. C-7 Cleat
 Complete Railing

* Indicated values will vary pending actual site and payload conditions.

QHSE Standards

ISO 9001:2015, ISO 14001:2015, ISO 45001:2018



The information contained herein is provided for general reference purposes only. Whilst we have taken every care to ensure the accuracy and quality of the above information, we can accept no responsibility in respect of any loss or damage of any kind whatsoever which may arise from your reliance on the information without our assistance. The information contained in this specification is protected by intellectual property law. As such any reproduction in whole or in part in whatever way or form is strictly prohibited without prior approval by Combifloat Systems B.V.



June 2021